

Specifications

Model name **PCG-FX605**

Model number **PCG-9E1M**


<i>Operating system</i>	Microsoft® Windows® XP Home Edition
<i>Processor</i>	1500+ Mobile AMD Athlon™ XP Processor featuring PowerNow!™
<i>Hard disk drive</i>	30 GB
<i>Standard RAM</i>	256 MB SDRAM (in slot)
<i>Maximum RAM</i>	512 MB
<i>LCD screen</i>	15.0" XGA (1024x768) TFT
<i>L2 cache memory</i>	256 KB (on die)
<i>MPEG</i>	MPEG 2 Digital Video Supports full-screen playback
<i>Graphics</i>	ATI 3D RAGE™ MOBILITY-M1 with 8 MB Video RAM and 3D accelerator
<i>Display</i>	Dual Display
<i>Sound capabilities</i>	16-bit CD-quality stereo sound
<i>Floppy disk drive</i>	3.5" 1.44 MB (internal)



Model name **PCG-FX605**

Model number **PCG-9E1M**

<i>CD-RW/DVD-ROM drive</i>	<p>CD-RW/DVD-ROM drive: up to 24x max. CD-ROM reading speed up to 8x max. CD-R writing speed up to 8x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed laser diode properties: wave length: DVD 656 nm, CD 785 nm laser output: DVD 4.85 μW (max), CD 151 μW</p>
<i>Internal modem</i>	built-in V.90/K56flex (56kbps) data/fax modem
<i>Telecommunication capabilities</i>	Ethernet network, PSTN data connectivity
<i>Expansion capabilities</i>	two PCMCIA type II or one type III Cards and Carbus support
<i>Built-in capabilities</i>	stereo speakers, touchpad
<i>Connection capabilities on notebook</i>	port replicator, monitor (VGA output), printer, external speakers or headphone, external microphone, 2 x type II PC Card slots or 1 x type III PC Card slot, 2 USB, serial port, TV Out, modem, i.LINK™ (IEEE1394) S400, Ethernet
<i>Supplied accessories</i>	rechargeable battery, AC adapter, AC power cord, phone cable, video cable, weight saver



Model name **PCG-FX605**

Model number **PCG-9E1M**

<i>Power source</i>	19.5V DC/AC100-240V
<i>Power management</i>	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)
<i>Battery</i>	Lithium ion
<i>Dimensions Width/Height/Depth</i>	324 mm / 38.5 mm to 54.1 mm / 265.5 mm
<i>Weight With 1 battery and weight saver With 1 battery and floppy disk drive</i>	3.20 kg 3.40 kg
<i>Operating temperature</i>	+5°C to +35°C (temperature gradient less than 10°C/hour)
<i>Storage temperature</i>	-20°C to +60°C (temperature gradient less than 10°C/hour)
<i>Operating humidity</i>	20% to 80% (not condensed), provided that humidity is less than 65% at +35°C (hygrometer reading of less than 29°C)
<i>Storage humidity</i>	10% to 90% (not condensed), provided that humidity is less than 20% at +60°C (hygrometer reading of less than 35°C)

Specifications are subject to change without notice.