



Specifications

Model name

PCG-VX71P

Model number

PCG-551M

<i>Operating system</i>	Microsoft® Windows® XP Professional
<i>Processor</i>	Low Voltage Mobile Intel® Pentium® III processor 850 MHz-M supports Enhanced SpeedStep Technology™
<i>Hard disk drive</i>	30 GB
<i>Standard RAM</i>	256 MB SDRAM (128 MB on board, 128 MB in slot)
<i>Maximum RAM</i>	384 MB
<i>LCD screen</i>	14.1" XGA (1024x768) TFT screen
<i>L2 cache memory</i>	512 KB (on die)
<i>Graphics</i>	Intel® 815EM Chipset with integrated graphics accelerator max. 11 MB video RAM (shared with main memory) with 3D accelerator
<i>Sound capabilities</i>	16-bit CD-quality stereo sound
<i>Internal modem</i>	Built-in V.90/K56Flex (56kbps) data/fax modem



Model name

PCG-VX71P

Model number

PCG-551M

<i>CD-RW/CD-ROM/DVD-ROM</i>	<p>i.LINK™ CD-RW/DVD-ROM drive up to 24x max. CD-ROM reading speed up to 8x max. CD-R writing speed up to 4x max. CD-RW writing speed up to 8x max. DVD-ROM reading speed</p> <p>laser diode properties: wave length: DVD 660 nm, CD-RW 785 nm laser output: 468 μW</p>
<i>Telecommunication capabilities</i>	Ethernet network, PSTN data connectivity
<i>Expansion capabilities</i>	One PC Card type I/II and CardBus support
<i>Built-in capabilities</i>	Stereo speakers, touchpad, Jog Dial™ with back button, MagicGate Memory Stick™
<i>Special buttons</i>	Jog Dial™, Wireless switch
<i>Connection capabilities on notebook</i>	External speakers/headphone (with MEGA BASS), external microphone, 2 USB ports, 1 type I or II PC Card slot, i.LINK™ (IEEE1394) S400, Ethernet (10 BASE-T/100 BASE-TX), modem, monitor (VGA) connector, MagicGate Memory Stick™
<i>Supplied accessories</i>	Rechargeable battery, AC adapter, AC power cord, i.LINK™ CD-RW/DVD-ROM drive, phone cable, phone plug



Model name

PCG-VX71P

Model number

PCG-551M

<i>Power management</i>	ENERGY STAR® compliant ACPI (Advanced Configuration & Power Interface)
<i>Power source</i>	16V / AC100 - 240V
<i>Battery</i>	6 cell-lithium ion
<i>Dimensions</i> <i>Width</i> <i>Height</i> <i>Depth</i>	312.8 mm 17.7 mm - 33.1 mm 261.5 mm
<i>Weight (with 1 battery)</i>	2.00 kg
<i>Operating temperature</i>	+5°C to +35°C (temperature gradient less than +10°C/hour)
<i>Storage temperature</i>	-20°C to +60°C (temperature gradient less than +10°C/hour)
<i>Operating humidity</i>	20% to 80% (not condensed), provided that humidity is less than 65% at +35°C (hygrometer reading of less than +29°C)
<i>Storage humidity</i>	10% to 90% (not condensed), provided that humidity is less than 20% at +60°C (hygrometer reading of less than +35°C)

Model name

PCG-VX71P

Model number

PCG-551M

<i>Wireless communication: Wireless LAN</i>	IEEE802.11b standard (Ad hoc peer-to-peer support)
<i>Usable frequency band</i>	2.4 GHz band (2.400 GHz - 2.462 GHz)
<i>Maximum communication speed (1)</i>	max. 11 Mbps
<i>Communication distance (2)</i>	10m to 100m (open space)
<i>Wireless channels</i>	From 1 to 11
<i>Modulation method</i>	DS-SS (IEEE802.11b standard)
<i>Length of network key (3)</i>	64, 128 bit

(1) The maximum communication speed of the IEEE802.11b standard can vary depending on the obstacles or the distance between the communication devices, the radio waves, the operating system or the software you use.

(2) The maximum communication distance can vary depending on the obstacles between the communication devices, the radio waves, the operating system or the software you use.

(3) You can type maximum of 5 letters (40 bits) and 13 characters (104 bits).

Specifications are subject to change without notice.